

HALO 2.9 Release Notes

Refer to the Administration Manual at <https://halodetect.com/resources/manuals-guides/> for details.

Version 2.9.0.10

- New Smoking Event has been added.
- Improvement to Presets creating more configurable control between choices.
- RTSP section has added the RTSP string to the display.

Version 2.8.3.6

- Improvement to PoE downstream reliability.

Version 2.8.2.3

- Support added for devices without a real time clock

Version 2.8.1.11

- Basic authentication over HTTPS is accepted for all functions.
- People Counting now has a method for detecting thermal decay.
- Masking detection improvements.
- Improved temperature compensation by orientation. (Wall or Ceiling).
- External Messaging is now Primary Integration. Secondary Integration has been added for dual integration.
- Updated Genetec Partner Integration for Primary and Secondary Integration and now also Heartbeat
 - New %ALLSENSORS% (comma separated list of all sensor name=value pairs), %ALLSENSORSNL% (new-line separated list of name=value pairs), and %ALLSENSORS@% (space delimited name=@value@ pairs) added for Integration, Heartbeat and Email use.
- An event UID field added to Events and %UID% keyword for Integration and Email.
- Additional Information fields added to device settings. Fields associate to keywords under integration, notifications and heartbeat messages.
- Korean language support added.
- Ethernet Out control and status added. Ability to disable Ethernet Out via UI.
- Graph view removed.
- Actions Tab view simplified by collapsing columns unused.
- BACnet Advanced Settings update: Custom port number, Foreign device BBMD address & TTL.
- Panic Button with Management UI.
- SMTP Security choices in new UI have been improved to support copying configuration between new and old halos.
- Change email radio security buttons into pulldown with added Ignore TLS option.
- Updated Masking, CO2 and Humidity icons for consistent style.